

P A T E N T C L A I M S

1. A sheet flashing member (1) comprising:
a sheet section (40) defining a plane and having first and second corner segments (20, 30),
5 at least one flange (11, 21) arranged at an angle relative to the plane of the sheet section and adapted to engage a surface of a roof penetrating building structure, c h a r a c t e r i z e d i n t h a t
10 at least one of said corner segments at a surface thereof comprises at least one indication (22, 32, 34, 38) indicating a pattern, such that at least a part of the sheet section may be separated from the remaining part of the flashing member along the indi-
15 cations in order to transform the respective corner segment from an initial state to a transformed state.
2. A sheet flashing member as defined in claim 1, wherein each said indication (22, 32, 34, 38) comprises a visual indication in the shape of at least
20 one longitudinally extending line or a longitudinally extending row of dots, short sections etc.
3. A sheet flashing member as defined in claim 1, wherein each said indication (22, 32, 34, 38) comprises a weakening section.
- 25 4. A sheet flashing member as defined in claim 3, wherein said weakening sections includes at least one groove.
5. A sheet flashing member as defined in claim 4, wherein said groove is formed by depression.
- 30 6. A sheet flashing member as defined in claim 3, wherein said weakening sections comprise a longitudinally extending cord member accommodated in the corner segment (20, 30).

7. A sheet flashing member as defined in any of the previous claims, wherein the pattern defines one or more indications delimiting an area (26, 37) of the end portion (20, 30) which, when separation has
5 taken place, thereby can be removed.

8. A sheet flashing member as defined in any of the previous claims, wherein the sheet section (40) has a general longitudinal orientation, the pattern defining at least one indication (38) arranged at an
10 oblique angle relative to the general longitudinal orientation, the oblique indication being directly or indirectly connected to a free edge (33, 35) of the sheet section.

9. A sheet flashing member as defined in any of
15 the previous claims, wherein the sheet section (40) includes a main portion (10) and the first and second end portions define first and second corner segments (20, 30), the main portion comprising an upstanding flange (11) and the first and second corner segments
20 comprising first and second flanges (21, 31) arranged substantially perpendicularly to the upstanding flange, the flanges (11, 21, 31) being adapted to engage a longitudinal surface portion of a roof penetrating building structure as well as its associated
25 corner portions.

10. A sheet flashing member as defined in claim 9, comprising a skirt element (50) which can be adapted to engage an upper roof surface.

11. A sheet flashing member as defined in claim
30 9 or 10, wherein the first corner segment (20) comprises an indication (22) arranged across the width thereof and generally perpendicularly to the general longitudinal orientation, and wherein the second cor-

ner segment (30) comprises first and second indications (32, 34) defining a portion (37), and a third indication (38) arranged at an oblique angle relative to the general longitudinal orientation and connected 5 to said portion.